




Slip/Docket Printer

Model TM - U295



Units:mm

The Atrax model TM-U295, slip printer is an ultra-compact versatile printer that can accept a range of docket sizes and multiple copy carbonised stationery.

Already installed by Atrax in many air cargo operations around the world it has proven itself most suitable for container close-out slips or printing on any manually placed forms.

Select from among four print sizes and four printing directions. Or, use page mode to tell the printer where to print on the page. The TM-U295 is also equipped with a host of user-friendly features, such as an easy-to-operate touch panel and an automatic paper eject function. And, for the widest range of applications, connect the TM-U295 to an intelligent Atrax scale readout.

World's Smallest Slip Printer

Measuring a mere 180 mm (W) x 190.5 mm (D) x 101.5 mm (H) and weighing in at only 1.6 kg, the TM-U295 is the world's smallest slip printer. The small size and simple design of this printer make it a good match for any printing application.

Variety of Printing Formats

With four character sizes and four printing directions, the TM-U295 flexibility adapts to your slip printing needs. Further, you can use page mode to print characters practically anywhere on the slip.

User Friendly

Features such as an easy-to-use touch panel and automatic paper feedout maximize user friendliness. In addition, the ASB function, which automatically sends the status of the printer, enables the operator to monitor the printer status.

Superb Reliability

EPSON's world-renowned quality and reliability are Reflected in every component and mechanism of the TM-U295, ensuring products unsurpassed in performance and dependability.

SPECIFICATIONS

Print Method:	7-pin, shuttle impact dot matrix
Print Font:	5 x 7 / 7 x 7
Column capacity:	35 / 42 columns
Character size:	1.6 (W) x 2.9 (H) / 1.3 (W) x 2.9 (H)mm
Character set:	95 Alphanumeric, 32 International, 128 x 3 Graphic
Characters Per Inch:	13.5 CPI / 16.2 CPI
Print Speed:	2.1 LPS
Data Buffer:	512 bytes or 35 bytes
Interface:	RS-232C / Bi-directional parallel
Paper Dimensions:	Slip: 80(W) x 69(L) to 182(W) x 257(L) mm
Paper Thickness:	0.09 to 0.35mm
Copy Capability:	One original and two copies
Inked Ribbon:	ERC-27 (purple)
Ribbon Life:	15 x 10 ⁵ characters
Power:	24 VDC ± 10%
Current Consumption:	Approx. 600 mA (mean)
D.K.D. Function:	2 drivers
Reliability: MTBF	18 x 10 ⁴ hours
MCBF	7 x 10 ⁶ lines
Overall Dimensions:	180 (W) x 190.5 (D) x 101.5 (H) mm
Weight:	Approx. 1.6 kg
EMC Standards:	VCCI class A, FCC class A, CE marking, AS / NZS 3548 class B
Safety Standards:	UL / CSA / TÜV (EN60950)

Atrax Group NZ Limited.

Telephone 64 9 634 5337, Facsimile: 64 9 634 5339,
E-mail: atrax@atraxgroup.com Internet: www.atraxgroup.com

R0901

ATRAX